



Product Data Sheet

Lexan® HPxxS Film

Description

Lexan HPxxS is a transparent high-performance one side coated polycarbonate film, which offers excellent chemical and abrasion resistance.

These performance capabilities, along with Lexan film's ease of processing, make HPxxS film very suitable for graphic applications such as:

- industrial nameplates
- business and communication equipment
- medical and diagnostic equipment
- pager/mobile phone LCD windows
- cluster and dial-lens covers
- appliance front-panels and overlays

Configuration

Gloss (%)	Gauges (mm)	Color
92	0.175	112
60	0.250	
40	0.375	
12	0.500	
	0.635	
	0.750	

Lexan HPxxS



Product Data Sheet

Lexan® HPxxS Film

Property	Test	Unit	Value+
Physical			
Density	ISO 1183	g/cm ³	1.20
Water absorption, saturation, 23°	ISO 62	%	0.40
Resistance to humidity, 720 hrs. @ 40°C, 100% RH	GE test	---	no visible change
Mechanical			
Tensile stress, yield	ISO 527	MPa	60
Tensile stress, break	ISO 527	MPa	70
Tear strength, initiation	ASTM D1004	kN/m	245
Tear strength, propagation	ASTM D1922	kN/m	10-20
Thermal			
Heat aging @ 168 hrs. 82°C	GE test	---	no visible change
Coefficient of linear expansion	DIN 53752	1/°C	7x10 ⁻⁵

Optical						
Property	Test Method	Units	Values+			
			HP92	HP60	HP40	HP12
Haze	ASTM D1003	%	<0.5	6.4	23	45
Light transmission	ASTM D1003	%	92	92	91	90
Yellowness index	ASTM D1925	--	0.8	0.8	0.9	1.2
Gloss back painted flat black	ASTM D523	Gardner				
60°			92	62	40	12
85°			--	--	--	45
20°			84	--	--	--
Gloss clear oven white	ASTM D523	Gardner				
60°			165	65	64	27
85°			--	--	--	--
20°			181	181	--	--

+ Typical values only. Variations within normal tolerances are possible for the various textures.

Product Data Sheet

Lexan® HPxxS Film

Chemical and Abrasion resistance

Chemical resistance	As manufactured	Post cured*
One hour continuous surface contact at 23°C		
Acetone	Failed	Passed
Methylethylketone	Failed	Passed
Toluene	Failed	Passed
Dichloromethane	Failed	Passed
Isopropyl alcohol	Passed	Passed
Cyclohexanone	Failed	Passed
Ethyl acetate	Failed	Passed
Xylene	Failed	Passed
Sodium hydroxide (40%)	Failed	Passed
Hydrochloric acid (conc.)	Passed	Passed
Gasoline (Leaded)	Passed	Passed
Gasoline (Unleaded)	Passed	Passed
Butyl Cellosolve	Failed	Passed
24 hour surface exposure at 50°C		
Coffee	Failed	Passed
Mustard	Failed	Passed
Ketchup	Passed	Passed
Tea	Passed	Passed
Tomato Juice	Passed	Passed
Lemon Juice	Passed	Passed
Grape Juice	Passed	Passed
Vinegar	Passed	Passed
Milk	Passed	Passed
Mild household detergent	Passed	Passed

Taber abrasion			
Condition	Units	As manufactured	Post cured*
CS10F wheel, 500 grams			
25 cycles	▲ % haze	1.7	1.0
50 cycles	▲ % haze	3.2	2.0
100 cycles	▲ % haze	6.5	4.1
200 cycles	▲ % haze	12.9	9.0

* Post cure conditions: one elliptical focused medium pressure mercury vapour lamp at 300 Watts/2.5 mm and a conveyer speed of 6 metres per minute.

AMERICAS

United States

GE Plastics
1 Plastics Avenue
Pittsfield, MA 01201
Tel. (1) (413) 448 5400

Brazil

GE Plastics South America
Av. Das Nacoes Unidas, 12995 - 20 Andar
Edificio Plaza Centenario
04578 - 000 Sao Paulo, Sp
Brazil
Tel. (55) 11 5505 2800
Fax (55) 11 5505 1757

Argentina

GE Plastics South America
Av. L.N. Alem 619 9 Piso
1001 Buenos Aires
Argentina
Tel. (54) 1 317 8753
Fax (54) 1 313 9560

EUROPE

European Headquarters

General Electric Plastics B.V. SPE
Plasticslaan 1
PO Box 117
NL - 4600 AC Bergen op Zoom
The Netherlands
Tel. (31) (164) 29 27 42
Fax (31) (164) 29 19 86

United Kingdom

GE Plastics Ltd
Old Hall Road
Sale
Cheshire M33 2HG
United Kingdom
Tel. (44) (161) 905 50 01
Fax (44) (161) 905 50 04

Italy

General Electric Plastics Italia S.p.A.
Viale Brianza 181
I - 20092 Cinisello Balsamo (Mi)
Italy
Tel. (39) 02 61 83 42 61
Fax (39) 02 61 83 42 09

Germany

General Electric Plastics GmbH
Eisenstraße 5
D - 65428 Rüsselsheim
Germany
Tel. (49) (61 42) 601 101
Fax (49) (61 42) 601 259

Spain

GET sl (Gestión y Especificaciones Técnicas)
Agente Oficial España y Portugal
C/Girona, 67, 3º-2a
08009 Barcelona
Spain
Tel. (34) (93) 488 03 18
Fax (34) (93) 487 32 36

France

General Electric Plastics France S.à.R.L.
Z.I. de St. Guénault B.P. 67
F - 91002 Evry-Cedex
France
Tel. (33) (1) 60 79 69 00
Fax (33) (1) 60 79 69 21

PACIFIC

Australia

GE Plastics (Australia) Pty. Ltd.
175 Hammond Road
Dandenong, Victoria 3175
Australia
Tel. (61) 39 794 4204
Fax (61) 39 794 8563

Beijing

GE Plastics
Citic Building, 3rd Floor
No. 19 Jian Guo Men Wai Avenue
Beijing 100004
China
Tel. (86) 10 6500 6538
Fax (86) 10 6500 6476

Guangzhou

GE Plastics Guangzhou
Room 1212, Yi An Plaza
No. 38, Jian She 6 Road
Guangzhou, 510060
China
Tel. (86) 20 8387 2818
Fax (86) 20 3128 or 3118

Hong Kong

GE Plastics Hong Kong Ltd.
Rm 1008, Tower 1, The Gateway
25 Canton Road
Kowloon
Hong Kong
Tel. (852) 26 29 0880
Fax (852) 26 29 0801

Indonesia

GE Plastics Indonesia
Menara Batavia 5th Floor,
JI KH Mas Manyur kav.126
Jakarta 10220
Indonesia
Tel. (62) 21 574 4980
Fax (62) 21 574 7101

Japan

SP Pacific Ltd.
Nihonbashi Hamacho Park Bldg. 5th Floor
2-35-4 Nihonbashi Hamacho
Chuo-ku, Tokyo 103
Japan
Tel. (81) 3 569 6301
Fax (81) 3 569 6306

Korea

GE Plastics Korea Co. Ltd.
#231-8 Nonhyun-Dong
Kangnam-Ku
Seoul 135-010
Korea
Tel. (822) 510 6273
Tel. (882) 510 6291
Fax (822) 510 6299

Shanghai

GE Plastics Shanghai
10th Floor, Shartex Center
88 Zunyi Road(s)
Shanghai 200335 China
Tel. (86) 21 6270 6789
Fax (86) 21 6270 9973
Fax (86) 21 6270 9974
Fax (86) 21 6270 9975

Singapore

GE Singapore
GE Tower, 240 Panjang Pagar Road
#500 Singapore 088540
Tel. (65) 326 3900
Fax (65) 326 3946

Taiwan

GE Plastics
13th Floor, #168
Tun Hua North Road
Taipei
Taiwan
Tel. (886) 2 514 9842
Fax (886) 2 514 9921

Thailand

GE Plastics Thailand
15th Floor, Thaniya Plaza Buiding
52 Silom Road, Bangkok 10500
Thailand
Tel. (662) 231 2918
Fax (662) 231 2322



GE Structured Products

www.GEStructuredProducts.com

All information, recommendation or advice contained in this document or given by General Electric Company, USA, or any of its subsidiaries, affiliates or authorised representatives, whether written or oral, is given in good faith, to the best of its knowledge and based on current procedures in effect. The products of General Electric Company or, if applicable, of its subsidiaries or affiliates are sold subject to Conditions of Sale, printed on the back of order acknowledgements, invoice or available upon request. Nothing in this or any other document shall alter, vary, supersede or operate to waive any of the Conditions of Sale. Each user of the products shall convince himself, through all available sources (including finished product testing in its appropriate environment) of the suitability of the products supplied for its own particular purpose. Because actual use of the products by the user is beyond the control of General Electric Company, its subsidiaries and affiliates, such use is within the exclusive responsibility of the user. General Electric Company, its subsidiaries and affiliates cannot be held responsible for any loss incurred through incorrect or faulty use of the products. Information, recommendation and/or advice are neither made to infringe on any patents, nor to grant a license under any patent or intellectual property right of General Electric Company or any of its subsidiaries or affiliated companies, nor to grant the right to file for any patent protection.

Lexan® is a Trademark of General Electric Co., USA.